

|   |                                       | TEMPERATURA ENTRADA PRIMARIO °C |                              | 55 °C |           | 70 °C |           | 80 °C |           | 90 °C |           |
|---|---------------------------------------|---------------------------------|------------------------------|-------|-----------|-------|-----------|-------|-----------|-------|-----------|
|   |                                       | modelo                          | caudal bomba primario (m³/h) | KW    | ACS (l/h) | KW    | ACS (l/h) | KW    | ACS (l/h) | KW    | ACS (l/h) |
| GEISER INOX - DOBLE PARED<br>[Producción ACS (litros/hora) en continuo 10°C - 45°C] | GX6 S/D/DEC 90                        | 2                               | 5                            | 123   | 11        | 271   | 14        | 344   | 18        | 443   |           |
|   |                                       | 3                               | 6                            | 148   | 12        | 295   | 15        | 369   | 20        | 492   |           |
|   |                                       | 5                               | 7                            | 172   | 13        | 320   | 17        | 418   | 22        | 541   |           |
|   | GX6 S/D/DEC 130                       | 2                               | 9                            | 221   | 19        | 468   | 25        | 615   | 32        | 787   |           |
|   |                                       | 3                               | 10                           | 246   | 20        | 492   | 27        | 664   | 34        | 837   |           |
|   |                                       | 5                               | 11                           | 271   | 22        | 541   | 30        | 738   | 37        | 910   |           |
|   | GX6 S/D/DEC 190                       | 2                               | 8                            | 197   | 18        | 443   | 25        | 615   | 32        | 787   |           |
|   |                                       | 3                               | 9                            | 221   | 20        | 492   | 27        | 664   | 35        | 861   |           |
|   |                                       | 5                               | 11                           | 271   | 22        | 541   | 30        | 738   | 39        | 960   |           |
|   | GX6 S/D/DEC 260                       | 2                               | 11                           | 271   | 25        | 615   | 33        | 812   | 44        | 1083  |           |
|   |                                       | 3                               | 12                           | 295   | 27        | 664   | 36        | 886   | 48        | 1181  |           |
|   |                                       | 5                               | 13                           | 320   | 29        | 714   | 41        | 1009  | 53        | 1304  |           |
|   | GX6 S/D/DEC 400                       | 2                               | 17                           | 418   | 33        | 812   | 45        | 1107  | 55        | 1353  |           |
|   |                                       | 4                               | 19                           | 468   | 38        | 935   | 53        | 1304  | 66        | 1624  |           |
|   |                                       | 6                               | 20                           | 492   | 41        | 1009  | 57        | 1403  | 72        | 1772  |           |
|   | GX6 S/D/DEC 600                       | 2                               | 20                           | 492   | 39        | 960   | 52        | 1280  | 66        | 1624  |           |
|   |                                       | 4                               | 22                           | 541   | 45        | 1107  | 60        | 1476  | 78        | 1919  |           |
|   |                                       | 6                               | 24                           | 591   | 48        | 1181  | 65        | 1599  | 85        | 2092  |           |
|   | GX6 TS180                             | 2                               | 9                            | 221   | 17        | 418   | 23        | 566   | 29        | 714   |           |
|   |                                       | 3                               | 10                           | 246   | 18        | 443   | 25        | 615   | 32        | 787   |           |
|   |                                       | 5                               | 11                           | 271   | 19        | 468   | 27        | 664   | 35        | 861   |           |
|   | GX6 TS240                             | 2                               | 10                           | 246   | 21        | 517   | 28        | 689   | 36        | 886   |           |
|   |                                       | 3                               | 11                           | 271   | 22        | 541   | 31        | 763   | 39        | 960   |           |
|   |                                       | 5                               | 13                           | 320   | 24        | 591   | 34        | 837   | 42        | 1033  |           |
| GEISER INOX - SERPENTÍN<br>[Producción ACS (litros/hora) en continuo 10°C - 45°C]   | GX-150-M1                             | 2                               | 11                           | 271   | 21        | 517   | 28        | 689   | 34        | 837   |           |
|   |                                       | 3                               | 12                           | 295   | 23        | 566   | 31        | 763   | 38        | 935   |           |
|   |                                       | 5                               | 13                           | 320   | 26        | 640   | 35        | 861   | 43        | 1058  |           |
|   | GX-200-M1                             | 2                               | 15                           | 369   | 28        | 689   | 37        | 910   | 47        | 1157  |           |
|   |                                       | 3                               | 16                           | 394   | 32        | 787   | 43        | 1058  | 53        | 1304  |           |
|   |                                       | 5                               | 18                           | 443   | 36        | 886   | 49        | 1206  | 61        | 1501  |           |
|   | GX-300-M1/M2*<br>*serpentin inferior  | 2                               | 15                           | 369   | 33        | 812   | 45        | 1107  | 56        | 1378  |           |
|   |                                       | 4                               | 18                           | 443   | 42        | 1033  | 56        | 1378  | 69        | 1698  |           |
|   |                                       | 6                               | 19                           | 468   | 47        | 1157  | 62        | 1526  | 77        | 1895  |           |
|   | GX-500-M1/M2*<br>*serpentin inferior  | 2                               | 20                           | 492   | 40        | 984   | 53        | 1304  | 66        | 1624  |           |
|   |                                       | 4                               | 23                           | 566   | 51        | 1255  | 67        | 1649  | 83        | 2042  |           |
|   |                                       | 6                               | 25                           | 615   | 58        | 1427  | 76        | 1870  | 93        | 2288  |           |
|   | GX-800-M1/M2*<br>*serpentin inferior  | 3                               | 33                           | 812   | 62        | 1526  | 79        | 1944  | 98        | 2411  |           |
|   |                                       | 5                               | 39                           | 960   | 72        | 1772  | 94        | 2313  | 116       | 2854  |           |
|   |                                       | 8                               | 44                           | 1083  | 82        | 2018  | 108       | 2658  | 132       | 3248  |           |
|   | GX-1000-M1/M2*<br>*serpentin inferior | 3                               | 40                           | 984   | 77        | 1895  | 101       | 2485  | 127       | 3125  |           |
|   |                                       | 5                               | 47                           | 1157  | 94        | 2313  | 124       | 3051  | 155       | 3814  |           |
|   |                                       | 8                               | 54                           | 1329  | 110       | 2707  | 145       | 3568  | 181       | 4454  |           |
|   | GX-300-M2**<br>**serpentin superior   | 2                               | 15                           | 369   | 27        | 664   | 36        | 886   | 45        | 1107  |           |
|   |                                       | 4                               | 17                           | 418   | 33        | 812   | 44        | 1083  | 55        | 1353  |           |
|   |                                       | 6                               | 18                           | 443   | 37        | 910   | 49        | 1206  | 61        | 1501  |           |
|   | GX-500-M2**<br>**serpentin superior   | 2                               | 15                           | 369   | 31        | 763   | 41        | 1009  | 50        | 1230  |           |
|   |                                       | 4                               | 18                           | 443   | 38        | 935   | 50        | 1230  | 61        | 1501  |           |
|   |                                       | 6                               | 20                           | 492   | 42        | 1033  | 56        | 1378  | 68        | 1673  |           |
|   | GX-800-M2**<br>*serpentin superior    | 2                               | 15                           | 369   | 31        | 763   | 41        | 1009  | 50        | 1230  |           |
|   |                                       | 4                               | 18                           | 443   | 38        | 935   | 50        | 1230  | 61        | 1501  |           |
|   |                                       | 6                               | 20                           | 492   | 42        | 1033  | 56        | 1378  | 68        | 1673  |           |
|   | GX-1000-M2**<br>**serpentin superior  | 2                               | 15                           | 369   | 31        | 763   | 41        | 1009  | 50        | 1230  |           |
|   |                                       | 4                               | 18                           | 443   | 38        | 935   | 50        | 1230  | 61        | 1501  |           |
|   |                                       | 6                               | 20                           | 492   | 42        | 1033  | 56        | 1378  | 68        | 1673  |           |
|   | GX-150-TSM                            | 2                               | 9                            | 221   | 19        | 468   | 25        | 615   | 32        | 787   |           |
|   |                                       | 4                               | 10                           | 246   | 22        | 541   | 30        | 738   | 37        | 910   |           |
|   |                                       | 6                               | 11                           | 271   | 24        | 591   | 32        | 787   | 41        | 1009  |           |
|   | GX-200-TSM                            | 2                               | 11                           | 271   | 24        | 591   | 31        | 763   | 39        | 960   |           |
|   |                                       | 4                               | 14                           | 344   | 30        | 738   | 38        | 935   | 47        | 1157  |           |
|   |                                       | 6                               | 15                           | 369   | 33        | 812   | 42        | 1033  | 52        | 1280  |           |

| TEMPERATURA ENTRADA PRIMARIO °C       |                              |  | 70 °C |           | 80 °C |           | 90 °C |           |
|---------------------------------------|------------------------------|--|-------|-----------|-------|-----------|-------|-----------|
| modelo                                | caudal bomba primario (m³/h) |  | KW    | ACS (l/h) | KW    | ACS (l/h) | KW    | ACS (l/h) |
| GX6 S/D/DEC 90                        | 2                            |  | 7     | 121       | 11    | 189       | 16    | 276       |
|                                       | 3                            |  | 8     | 138       | 12    | 207       | 17    | 293       |
|                                       | 5                            |  | 9     | 155       | 13    | 224       | 18    | 310       |
| GX6 S/D/DEC 130                       | 2                            |  | 13    | 224       | 20    | 344       | 27    | 465       |
|                                       | 3                            |  | 14    | 241       | 21    | 362       | 29    | 500       |
|                                       | 5                            |  | 16    | 276       | 23    | 396       | 32    | 551       |
| GX6 S/D/DEC 190                       | 2                            |  | 13    | 224       | 20    | 344       | 27    | 465       |
|                                       | 3                            |  | 15    | 258       | 22    | 379       | 29    | 500       |
|                                       | 5                            |  | 16    | 276       | 24    | 413       | 32    | 551       |
| GX6 S/D/DEC 260                       | 2                            |  | 18    | 310       | 27    | 465       | 35    | 603       |
|                                       | 3                            |  | 20    | 344       | 29    | 500       | 39    | 672       |
|                                       | 5                            |  | 22    | 379       | 32    | 551       | 43    | 741       |
| GX6 S/D/DEC 400                       | 2                            |  | 23    | 396       | 36    | 620       | 47    | 810       |
|                                       | 4                            |  | 27    | 465       | 42    | 723       | 55    | 947       |
|                                       | 6                            |  | 29    | 500       | 46    | 792       | 60    | 1033      |
| GX6 S/D/DEC 600                       | 2                            |  | 27    | 465       | 42    | 723       | 57    | 982       |
|                                       | 4                            |  | 32    | 551       | 48    | 827       | 66    | 1137      |
|                                       | 6                            |  | 34    | 586       | 52    | 896       | 72    | 1240      |
| GX6 TS180                             | 2                            |  | 12    | 207       | 18    | 310       | 25    | 431       |
|                                       | 3                            |  | 13    | 224       | 20    | 344       | 27    | 465       |
|                                       | 5                            |  | 14    | 241       | 21    | 362       | 29    | 500       |
| GX6 TS240                             | 2                            |  | 15    | 258       | 23    | 396       | 31    | 534       |
|                                       | 3                            |  | 16    | 276       | 25    | 431       | 33    | 568       |
|                                       | 5                            |  | 17    | 293       | 27    | 465       | 35    | 603       |
| GX-150-M1                             | 2                            |  | 15    | 258       | 23    | 396       | 29    | 500       |
|                                       | 3                            |  | 17    | 293       | 25    | 431       | 32    | 551       |
|                                       | 5                            |  | 18    | 310       | 28    | 482       | 36    | 620       |
| GX-200-M1                             | 2                            |  | 21    | 362       | 31    | 534       | 40    | 689       |
|                                       | 3                            |  | 24    | 413       | 35    | 603       | 45    | 775       |
|                                       | 5                            |  | 28    | 482       | 40    | 689       | 52    | 896       |
| GX-300-M1/M2*<br>*serpentin inferior  | 2                            |  | 24    | 413       | 36    | 620       | 47    | 810       |
|                                       | 4                            |  | 30    | 517       | 44    | 758       | 58    | 999       |
|                                       | 6                            |  | 33    | 568       | 49    | 844       | 65    | 1120      |
| GX-500-M1/M2*<br>*serpentin inferior  | 2                            |  | 30    | 517       | 44    | 758       | 57    | 982       |
|                                       | 4                            |  | 37    | 637       | 55    | 947       | 70    | 1206      |
|                                       | 6                            |  | 40    | 689       | 61    | 1051      | 78    | 1344      |
| GX-800-M1/M2*<br>*serpentin inferior  | 3                            |  | 44    | 758       | 63    | 1085      | 83    | 1430      |
|                                       | 5                            |  | 51    | 878       | 74    | 1275      | 98    | 1688      |
|                                       | 8                            |  | 58    | 999       | 83    | 1430      | 112   | 1929      |
| GX-1000-M1/M2*<br>*serpentin inferior | 3                            |  | 57    | 982       | 83    | 1430      | 109   | 1878      |
|                                       | 5                            |  | 68    | 1171      | 99    | 1705      | 132   | 2274      |
|                                       | 8                            |  | 78    | 1344      | 115   | 1981      | 153   | 2635      |
| GX-300-M2**<br>**serpentin superior   | 2                            |  | 18    | 310       | 30    | 517       | 38    | 655       |
|                                       | 4                            |  | 22    | 379       | 36    | 620       | 46    | 792       |
|                                       | 6                            |  | 24    | 413       | 40    | 689       | 51    | 878       |
| GX-500-M2**<br>**serpentin superior   | 2                            |  | 21    | 362       | 34    | 586       | 44    | 758       |
|                                       | 4                            |  | 26    | 448       | 41    | 706       | 53    | 913       |
|                                       | 6                            |  | 29    | 500       | 45    | 775       | 59    | 1016      |
| GX-800-M2**<br>**serpentin superior   | 2                            |  | 21    | 362       | 34    | 586       | 44    | 758       |
|                                       | 4                            |  | 26    | 448       | 41    | 706       | 53    | 913       |
|                                       | 6                            |  | 29    | 500       | 45    | 775       | 59    | 1016      |
| GX-1000-M2**<br>**serpentin superior  | 2                            |  | 21    | 362       | 34    | 586       | 44    | 758       |
|                                       | 4                            |  | 26    | 448       | 41    | 706       | 53    | 913       |
|                                       | 6                            |  | 29    | 500       | 45    | 775       | 59    | 1016      |
| GX-150-TSM                            | 2                            |  | 13    | 224       | 20    | 344       | 27    | 465       |
|                                       | 4                            |  | 16    | 276       | 24    | 413       | 32    | 551       |
|                                       | 6                            |  | 17    | 293       | 26    | 448       | 34    | 586       |
| GX-200-TSM                            | 2                            |  | 17    | 293       | 25    | 431       | 33    | 568       |
|                                       | 4                            |  | 21    | 362       | 30    | 517       | 40    | 689       |
|                                       | 6                            |  | 24    | 413       | 34    | 586       | 44    | 758       |

|   | TEMPERATURA ENTRADA PRIMARIO °C |                              | 55 °C |           | 70 °C |           | 80 °C |           | 90 °C |           |
|---|---------------------------------|------------------------------|-------|-----------|-------|-----------|-------|-----------|-------|-----------|
|   | modelo                          | caudal bomba primario (m³/h) | KW    | ACS (l/h) | KW    | ACS (l/h) | KW    | ACS (l/h) | KW    | ACS (l/h) |
| GEISER INOX - DOBLE PARED<br>[Producción ACS (litros/hora) en continuo 10°C - 45°C] | GX6 DE 140                      | 2                            | 8     | 205       | 18    | 450       | 24    | 625       | 32    | 790       |
|   |                                 | 4                            | 10    | 250       | 21    | 500       | 28    | 700       | 36    | 880       |
|   |                                 | 6                            | 12    | 300       | 23    | 555       | 31    | 750       | 39    | 950       |
|   | GX6 DE 180                      | 2                            | 9     | 210       | 19    | 460       | 25    | 630       | 33    | 795       |
|   |                                 | 4                            | 11    | 255       | 21    | 510       | 29    | 710       | 36    | 890       |
|   |                                 | 6                            | 13    | 305       | 23    | 560       | 31    | 750       | 40    | 960       |
|   | GX6 DE 215                      | 2                            | 11    | 300       | 26    | 620       | 34    | 820       | 45    | 1105      |
|   |                                 | 4                            | 13    | 320       | 30    | 720       | 41    | 995       | 53    | 1300      |
|   |                                 | 6                            | 15    | 350       | 32    | 795       | 44    | 1090      | 56    | 1390      |
|   | GX6 DE 260                      | 3                            | 16    | 400       | 31    | 790       | 44    | 1070      | 54    | 1305      |
|   |                                 | 5                            | 18    | 420       | 35    | 870       | 49    | 1180      | 59    | 1405      |
|   |                                 | 8                            | 19    | 440       | 38    | 925       | 51    | 1270      | 65    | 1600      |
|   | GX6 DE 400                      | 3                            | 19    | 450       | 36    | 900       | 50    | 1210      | 61    | 1510      |
|   |                                 | 5                            | 20    | 495       | 41    | 1010      | 55    | 1350      | 66    | 1670      |
|   |                                 | 8                            | 21    | 510       | 44    | 1050      | 60    | 1505      | 75    | 1860      |
|   | GX6 DE 600                      | 3                            | 21    | 550       | 41    | 1005      | 56    | 1370      | 71    | 1800      |
|   |                                 | 5                            | 22    | 580       | 45    | 1120      | 61    | 1510      | 81    | 2000      |
|   |                                 | 8                            | 24    | 600       | 50    | 1210      | 68    | 1660      | 90    | 2200      |
|   | GX6 DE 1000                     | 2                            | 25    | 625       | 45    | 1100      | 65    | 1600      | 95    | 2330      |
|   |                                 | 4                            | 37    | 900       | 58    | 1400      | 85    | 2075      | 118   | 2900      |
|   |                                 | 6                            | 40    | 1000      | 65    | 1600      | 93    | 2300      | 132   | 3250      |
|   | GX6 PAC/P 300                   | 2                            | 8     | 200       | 16    | 400       | 24    | 600       | 30    | 740       |
|   |                                 | 4                            | 10    | 245       | 19    | 455       | 26    | 650       | 35    | 860       |
|   |                                 | 6                            | 11    | 265       | 21    | 500       | 30    | 725       | 37    | 915       |
|   | GX6 PAC/P 400                   | 2                            | 8     | 200       | 17    | 425       | 25    | 610       | 33    | 805       |
|   |                                 | 4                            | 10    | 245       | 20    | 485       | 27    | 690       | 35    | 860       |
|   |                                 | 6                            | 11    | 265       | 22    | 545       | 32    | 775       | 40    | 980       |
|   | GX6 PAC/P 600                   | 2                            | 9     | 240       | 22    | 545       | 29    | 735       | 40    | 985       |
|   |                                 | 4                            | 11    | 275       | 26    | 645       | 34    | 850       | 46    | 1150      |
|   |                                 | 6                            | 13    | 320       | 28    | 700       | 36    | 915       | 49    | 1210      |
| GEISER INOX - SERPENTÍN<br>[Producción ACS (litros/hora) en continuo 10°C - 45°C]   | GX-200-HL                       | 2                            | 25    | 614       | 47    | 1145      | 61    | 1511      | 78    | 1909      |
|   |                                 | 4                            | 32    | 776       | 60    | 1484      | 81    | 1987      | 100   | 2473      |
|   |                                 | 6                            | 35    | 872       | 69    | 1688      | 92    | 2272      | 114   | 2810      |
|   | GX-300-HL                       | 2                            | 30    | 749       | 58    | 1432      | 75    | 1850      | 95    | 2348      |
|   |                                 | 4                            | 40    | 986       | 76    | 1861      | 98    | 2416      | 126   | 3095      |
|   |                                 | 6                            | 46    | 1127      | 86    | 2118      | 112   | 2755      | 144   | 3543      |
|   | GX-800-HL/HLB                   | 3                            | 56    | 1383      | 101   | 2479      | 125   | 3080      | 152   | 3728      |
|   |                                 | 5                            | 67    | 1660      | 125   | 3076      | 154   | 3791      | 182   | 4478      |
|   |                                 | 8                            | 78    | 1919      | 148   | 3635      | 181   | 4457      | 211   | 5181      |
|   | GX-1000-HL/HLB                  | 3                            | 58    | 1428      | 106   | 2603      | 131   | 3212      | 158   | 3891      |
|   |                                 | 5                            | 69    | 1704      | 129   | 3187      | 159   | 3924      | 192   | 4722      |
|   |                                 | 8                            | 80    | 1961      | 152   | 3732      | 187   | 4590      | 224   | 5501      |

| TEMPERATURA ENTRADA PRIMARIO °C |                              |     | 70 °C |           | 80 °C |           | 90 °C |           |
|---------------------------------|------------------------------|-----|-------|-----------|-------|-----------|-------|-----------|
| modelo                          | caudal bomba primario (m³/h) |     | KW    | ACS (l/h) | KW    | ACS (l/h) | KW    | ACS (l/h) |
| GX6 DE 140                      | 2                            | 12  | 205   | 20        | 345   | 26        | 455   |           |
|                                 | 4                            | 15  | 255   | 22        | 375   | 31        | 525   |           |
|                                 | 6                            | 16  | 275   | 24        | 405   | 32        | 555   |           |
| GX6 DE 180                      | 2                            | 13  | 225   | 21        | 355   | 26        | 460   |           |
|                                 | 4                            | 16  | 260   | 22        | 390   | 31        | 530   |           |
|                                 | 6                            | 17  | 275   | 24        | 415   | 33        | 555   |           |
| GX6 DE 215                      | 2                            | 19  | 315   | 30        | 520   | 37        | 645   |           |
|                                 | 4                            | 22  | 385   | 34        | 585   | 44        | 755   |           |
|                                 | 6                            | 24  | 410   | 36        | 605   | 47        | 810   |           |
| GX6 DE 260                      | 3                            | 22  | 345   | 34        | 600   | 45        | 760   |           |
|                                 | 5                            | 25  | 430   | 37        | 650   | 50        | 855   |           |
|                                 | 8                            | 26  | 455   | 40        | 700   | 55        | 950   |           |
| GX6 DE 400                      | 3                            | 25  | 440   | 40        | 695   | 51        | 890   |           |
|                                 | 5                            | 28  | 490   | 44        | 750   | 57        | 1000  |           |
|                                 | 8                            | 30  | 505   | 47        | 805   | 61        | 1055  |           |
| GX6 DE 600                      | 3                            | 29  | 500   | 45        | 780   | 61        | 1070  |           |
|                                 | 5                            | 32  | 550   | 50        | 860   | 70        | 1200  |           |
|                                 | 8                            | 35  | 600   | 55        | 910   | 76        | 1300  |           |
| GX6 DE 1000                     | 2                            | 32  | 580   | 55        | 950   | 82        | 1400  |           |
|                                 | 4                            | 41  | 700   | 68        | 1180  | 105       | 1740  |           |
|                                 | 6                            | 46  | 800   | 75        | 1300  | 112       | 1910  |           |
| GX6 PAC/P 300                   | 2                            | 11  | 200   | 18        | 310   | 25        | 425   |           |
|                                 | 4                            | 14  | 225   | 21        | 360   | 30        | 515   |           |
|                                 | 6                            | 15  | 250   | 23        | 385   | 32        | 550   |           |
| GX6 PAC/P 400                   | 2                            | 13  | 230   | 21        | 360   | 26        | 460   |           |
|                                 | 4                            | 15  | 255   | 24        | 395   | 31        | 525   |           |
|                                 | 6                            | 18  | 305   | 25        | 425   | 34        | 560   |           |
| GX6 PAC/P 600                   | 2                            | 14  | 250   | 24        | 400   | 31        | 530   |           |
|                                 | 4                            | 18  | 310   | 28        | 480   | 37        | 635   |           |
|                                 | 6                            | 19  | 320   | 30        | 520   | 40        | 690   |           |
| GX-200-HL                       | 2                            | 34  | 585   | 50        | 864   | 67        | 1155  |           |
|                                 | 4                            | 43  | 745   | 81        | 65    | 86        | 1478  |           |
|                                 | 6                            | 49  | 842   | 74        | 1279  | 97        | 1671  |           |
| GX-300-HL                       | 2                            | 43  | 747   | 62        | 1072  | 83        | 1434  |           |
|                                 | 4                            | 55  | 945   | 80        | 1377  | 108       | 1858  |           |
|                                 | 6                            | 62  | 1065  | 90        | 1556  | 123       | 2114  |           |
| GX-800-HL/HLB                   | 3                            | 76  | 1303  | 105       | 1801  | 133       | 2292  |           |
|                                 | 5                            | 92  | 1586  | 126       | 2175  | 157       | 2707  |           |
|                                 | 8                            | 107 | 1844  | 147       | 2532  | 180       | 3100  |           |
| GX-1000-HL/HLB                  | 3                            | 80  | 1385  | 109       | 1882  | 139       | 2392  |           |
|                                 | 5                            | 95  | 1644  | 131       | 2260  | 166       | 2855  |           |
|                                 | 8                            | 110 | 1896  | 151       | 2609  | 191       | 3297  |           |



## GEISER INOX - DOBLE PARED modelos - S/D/DE/DEC/P/PAC - (Producción ACS - caudal punta -)

|  |        | GX6<br>S/D/DEC 90 | GX6<br>S/D/DEC 130 | GX6<br>S/D/DEC 190 | GX6<br>S/D/DEC 260 | GX6<br>S/D/DEC 400 | GX6<br>S/D/DEC 600 |
|--|--------|-------------------|--------------------|--------------------|--------------------|--------------------|--------------------|
| Caudal punta a 40°C                    | L/10'  | 120               | 203                | 315                | 380                | 575                | 900                |
| Caudal punta a 45°C                    | L/10'  | 102               | 175                | 270                | 325                | 490                | 770                |
| Caudal punta a 60°C                    | L/10'  | 72                | 122                | 190                | 225                | 344                | 539                |
| Caudal punta a 40°C                    | L/60'  | 590               | 1000               | 1132               | 1545               | 2135               | 2755               |
| Caudal punta a 45°C                    | L/60'  | 495               | 840                | 954                | 1290               | 1790               | 2310               |
| Caudal punta a 60°C                    | L/60'  | 295               | 515                | 590                | 755                | 1075               | 1400               |
| Caudal continuo a 40°C                 | Ltrs/h | 565               | 960                | 980                | 1400               | 1875               | 2225               |
| Caudal continuo a 45°C                 | Ltrs/h | 470               | 800                | 820                | 1160               | 1560               | 1850               |
| Caudal continuo a 60°C                 | Ltrs/h | 265               | 470                | 480                | 635                | 875                | 1040               |
| Tiempo de calentamiento (de 10 a 75°C) | Min    | 28                | 31                 | 45                 | 47                 | 50                 | 56                 |
| Caudal de agua de calefacción          | m³/h   | 5                 | 5                  | 5                  | 6                  | 6                  | 6                  |

Tª Impulsión del agua de calefacción 85°C

|  |        | GX6 DE140 | GX6 DE180 | GX6 DE215 | GX6 DE260 | GX6 DE400 | GX6 DE600 |
|--|--------|-----------|-----------|-----------|-----------|-----------|-----------|
| Caudal punta a 40°C                    | L/10'  | 203       | 315       | 475       | 530       | 575       | 900       |
| Caudal punta a 45°C                    | L/10'  | 175       | 270       | 415       | 440       | 490       | 770       |
| Caudal punta a 60°C                    | L/10'  | 122       | 190       | 250       | 265       | 344       | 539       |
| Caudal punta a 40°C                    | L/60'  | 935       | 1190      | 1675      | 1875      | 2175      | 2790      |
| Caudal punta a 45°C                    | L/60'  | 785       | 1000      | 1415      | 1565      | 1820      | 2345      |
| Caudal punta a 60°C                    | L/60'  | 465       | 605       | 795       | 925       | 1100      | 1435      |
| Caudal continuo a 40°C                 | Ltrs/h | 880       | 1050      | 1440      | 1620      | 1920      | 2270      |
| Caudal continuo a 45°C                 | Ltrs/h | 735       | 880       | 1200      | 1350      | 1600      | 1890      |
| Caudal continuo a 60°C                 | Ltrs/h | 415       | 500       | 653       | 790       | 905       | 1075      |
| Tiempo de calentamiento (de 10 a 75°C) | Min    | 31        | 41        | 37        | 37        | 50        | 56        |
| Caudal de agua de calefacción          | m³/h   | 2,6       | 3,5       | 4,2       | 5,5       | 6,4       | 7,2       |

Tª Impulsión del agua de calefacción 85°C

|  |        | GX6 P300 | GX6 P400 | GX6 P600 | GX6 P800 | GX6 P1000 |  |
|--|--------|----------|----------|----------|----------|-----------|--|
| Caudal punta a 40°C                    | L/10'  | 251      | 320      | 465      | 433      | 540       |  |
| Caudal punta a 45°C                    | L/10'  | 215      | 275      | 400      | 370      | 465       |  |
| Caudal punta a 60°C                    | L/10'  | 150      | 190      | 280      | 260      | 325       |  |
| Caudal punta a 40°C                    | L/60'  | 965      | 1080     | 1360     | 1495     | 1875      |  |
| Caudal punta a 45°C                    | L/60'  | 815      | 910      | 1150     | 1250     | 1570      |  |
| Caudal punta a 60°C                    | L/60'  | 500      | 555      | 710      | 785      | 970       |  |
| Caudal continuo a 40°C                 | Ltrs/h | 860      | 915      | 1075     | 1275     | 1600      |  |
| Caudal continuo a 45°C                 | Ltrs/h | 720      | 760      | 900      | 1060     | 1325      |  |
| Caudal continuo a 60°C                 | Ltrs/h | 420      | 440      | 520      | 630      | 775       |  |
| Tiempo de calentamiento (de 10 a 75°C) | Min    | 40       | 48       | 55       | 47       | 48        |  |
| Caudal de agua de calefacción          | m³/h   | 3        | 3        | 3        | 5        | 5         |  |

Tª Impulsión del agua de calefacción 85°C

|  |        | GX6 PAC300 | GX6 PAC400 | GX6 PAC600 | GX6 PAC800 | GX6 PAC1000 |  |
|--|--------|------------|------------|------------|------------|-------------|--|
| Caudal punta a 40°C                    | L/10'  | 250        | 315        | 600        | 433        | 540         |  |
| Caudal punta a 45°C                    | L/10'  | 215        | 270        | 515        | 370        | 465         |  |
| Caudal punta a 60°C                    | L/10'  | 150        | 190        | 360        | 260        | 325         |  |
| Caudal punta a 40°C                    | L/60'  | 1050       | 1165       | 1650       | 1495       | 1875        |  |
| Caudal punta a 45°C                    | L/60'  | 880        | 975        | 1390       | 1250       | 1570        |  |
| Caudal punta a 60°C                    | L/60'  | 525        | 585        | 870        | 785        | 970         |  |
| Caudal continuo a 40°C                 | Ltrs/h | 960        | 1020       | 1260       | 1275       | 1600        |  |
| Caudal continuo a 45°C                 | Ltrs/h | 800        | 850        | 1050       | 1060       | 1325        |  |
| Caudal continuo a 60°C                 | Ltrs/h | 450        | 475        | 610        | 630        | 775         |  |
| Tiempo de calentamiento (de 10 a 75°C) | Min    | 40         | 48         | 54         | 47         | 48          |  |
| Caudal de agua de calefacción          | m³/h   | 5          | 5          | 5          | 5          | 5           |  |

Tª Impulsión del agua de calefacción 85°C

| GEISER INOX, producción ACS<br>caudal punta |        | DOBLE PARED<br>modelos TS |           | SERPENTÍN<br>modelos TSM |            |
|---|--------|---------------------------|-----------|--------------------------|------------|
|   |        | GX6 TS180                 | GX6 TS240 | GX-150-TSM               | GX-200-TSM |
| Caudal punta a 40°C                         | L/10'  | 238                       | 303       | 320                      | 410        |
| Caudal punta a 45°C                         | L/10'  | 204                       | 260       | 275                      | 350        |
| Caudal punta a 60°C                         | L/10'  | 143                       | 182       | 195                      | 245        |
| Caudal punta a 40°C                         | L/60'  | 994                       | 1238      | 1185                     | 1510       |
| Caudal punta a 45°C                         | L/60'  | 834                       | 1039      | 995                      | 1270       |
| Caudal punta a 60°C                         | L/60'  | 505                       | 629       | 610                      | 775        |
| Caudal continuo a 40°C                      | Ltrs/h | 908                       | 1122      | 1040                     | 1325       |
| Caudal continuo a 45°C                      | Ltrs/h | 757                       | 935       | 865                      | 1105       |
| Caudal continuo a 60°C                      | Ltrs/h | 435                       | 537       | 500                      | 635        |
| Tiempo de calentamiento (de 10 a 75°C)      | Min    | 44                        | 46        | 37                       | 42         |
| Caudal de agua de calefacción               | m³/h   | 5                         | 6         | 5                        | 6          |

Tª Impulsión del agua de calefacción 85°C

| GEISER INOX - <b>SERPENTÍN</b> modelos - <b>M1/M2/HL</b> - (Producción ACS - <b>caudal punta</b> -) |        |                      |                      |                      |                      |                      |                      |                       |                       |                        |
|---|--------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|-----------------------|-----------------------|------------------------|
|   |        | <b>GX-150<br/>M1</b> | <b>GX-200<br/>M1</b> | <b>GX-300<br/>M1</b> | <b>GX-400<br/>M1</b> | <b>GX-500<br/>M1</b> | <b>GX-800<br/>M1</b> | <b>GX-1000<br/>M1</b> | <b>GX-800<br/>M1B</b> | <b>GX-1000<br/>M1B</b> |
| Caudal punta a 40°C   | L/10'  | 315                  | 425                  | 600                  | 823                  | 1007                 | 1690                 | 1995                  | 1692                  | 1995                   |
| Caudal punta a 45°C   | L/10'  | 270                  | 364                  | 515                  | 705                  | 863                  | 1450                 | 1710                  | 1450                  | 1710                   |
| Caudal punta a 60°C   | L/10'  | 190                  | 255                  | 360                  | 494                  | 604                  | 1015                 | 1195                  | 1015                  | 1197                   |
| Caudal punta a 40°C   | L/60'  | 1265                 | 1840                 | 2310                 | 2865                 | 3050                 | 4610                 | 5950                  | 4610                  | 5950                   |
| Caudal punta a 45°C   | L/60'  | 1060                 | 1530                 | 1910                 | 2410                 | 2570                 | 3860                 | 5000                  | 3860                  | 5000                   |
| Caudal punta a 60°C   | L/60'  | 645                  | 930                  | 1170                 | 1475                 | 1580                 | 2370                 | 3110                  | 2370                  | 3110                   |
| Caudal continuo a 40°C  | Ltrs/h | 1140                 | 1700                 | 2050                 | 2450                 | 2450                 | 3500                 | 4750                  | 3500                  | 4750                   |
| Caudal continuo a 45°C  | Ltrs/h | 950                  | 1400                 | 1675                 | 2050                 | 2050                 | 2900                 | 3950                  | 2900                  | 3950                   |
| Caudal continuo a 60°C  | Ltrs/h | 550                  | 810                  | 975                  | 1175                 | 1175                 | 1625                 | 2300                  | 1625                  | 2300                   |
| Tiempo de calentamiento (de 10 a 75°C)  | Min    | 35                   | 37                   | 45                   | 40                   | 50                   | 52                   | 58                    | 52                    | 58                     |
| Caudal de agua de calefacción   | m³/h   | 5                    | 6                    | 6                    | 6                    | 6                    | 8                    | 8                     | 8                     | 8                      |

Tª Impulsión del agua de calefacción 85°C

| SERPENTÍN INFERIOR                     |        | GX-300<br>M2 | GX-400<br>M2 | GX-500<br>M2 | GX-800<br>M2 | GX-1000<br>M2 | GX-800<br>M2B | GX-1000<br>M2B |
|--|--------|--------------|--------------|--------------|--------------|---------------|---------------|----------------|
| Caudal punta a 40°C                    | L/10'  | 600          | 823          | 1007         | 1692         | 1995          | 1692          | 1995           |
| Caudal punta a 45°C                    | L/10'  | 515          | 705          | 863          | 1450         | 1710          | 1450          | 1710           |
| Caudal punta a 60°C                    | L/10'  | 360          | 494          | 604          | 1015         | 1197          | 1015          | 1197           |
| Caudal punta a 40°C                    | L/60'  | 2310         | 2865         | 3050         | 4610         | 5950          | 4610          | 5950           |
| Caudal punta a 45°C                    | L/60'  | 1910         | 2410         | 2570         | 3860         | 5000          | 3860          | 5000           |
| Caudal punta a 60°C                    | L/60'  | 1170         | 1475         | 1580         | 2370         | 3110          | 2370          | 3110           |
| Caudal continuo a 40°C                 | Ltrs/h | 2050         | 2450         | 2450         | 3500         | 4750          | 3500          | 4750           |
| Caudal continuo a 45°C                 | Ltrs/h | 1675         | 2050         | 2050         | 2900         | 3950          | 2900          | 3950           |
| Caudal continuo a 60°C                 | Ltrs/h | 975          | 1175         | 1175         | 1625         | 2300          | 1625          | 2300           |
| Tiempo de calentamiento (de 10 a 75°C) | Min    | 45           | 40           | 50           | 52           | 58            | 52            | 58             |
| Caudal de agua de calefacción          | m³/h   | 6            | 6            | 6            | 8            | 8             | 8             | 8              |

Tª Impulsión del agua de calefacción 85°C

|  |        | GX-200<br>HL | GX-300<br>HL | GX-400<br>M2 | GX-500<br>HL | GX-800<br>HL/HLB | GX-1000<br>HL/HLB |
|--|--------|--------------|--------------|--------------|--------------|------------------|-------------------|
| Caudal punta a 40°C                    | L/10'  | 580          | 800          | 1040         | 1200         | 1770             | 2115              |
| Caudal punta a 45°C                    | L/10'  | 490          | 675          | 880          | 1015         | 1505             | 1800              |
| Caudal punta a 60°C                    | L/10'  | 320          | 455          | 590          | 690          | 1035             | 1245              |
| Caudal punta a 40°C                    | L/60'  | 3285         | 4135         | 5175         | 5310         | 6780             | 7315              |
| Caudal punta a 45°C                    | L/60'  | 2695         | 3395         | 4260         | 4375         | 5590             | 6040              |
| Caudal punta a 60°C                    | L/60'  | 1625         | 2079         | 2605         | 2690         | 3455             | 3760              |
| Caudal continuo a 40°C                 | Ltrs/h | 3115         | 3850         | 4790         | 4790         | 5890             | 6170              |
| Caudal continuo a 45°C                 | Ltrs/h | 2540         | 3150         | 3920         | 3920         | 4820             | 5045              |
| Caudal continuo a 60°C                 | Ltrs/h | 1475         | 1840         | 2300         | 2300         | 2820             | 2955              |
| Tiempo de calentamiento (de 10 a 75°C) | Min    | 26           | 32           | 35           | 39           | 45               | 54                |
| Caudal de agua de calefacción          | m³/h   | 6            | 6            | 6            | 6            | 8                | 8                 |

Tª Impulsión del agua de calefacción 85°C